

Cone Crusher Yield Optimization

Magnus Evertsson



Improving Processes. Instilling Expertise.



Objectives


- **Different levels of optimization**
- **Different aspects of optimization**
- **Detailed demonstration of cone crusher yield optimization including economical aspects**

Crushing Plant Optimization

- large scale

Crushing Plant Optimization

- Technical and economical




Crushing Plant Optimization

The effect of wear

- Screen cloths
- Crushing chambers


Effect of Wear

The variation due to ONE wear part



Effect of Wear

The variation due to SIX different wear parts




Effect of Wear

Take home message:


To catch the true value you have to do several tests.

The combined effect will be normally distributed...

It can be handled mathematically and thus optimized!



Effect of Wear



Small wear tolerance

- + High average performance
- High replacements costs
- Frequent stops

Large wear tolerance

- + Low average performance
- High utilisation of wear parts
- More production time

Crushing Plant Optimization

- Concurrent ECONOMICAL and TECHNICAL optimization
- Wear management of parts
 - screen cloths
 - crushing chambers
- Make the most out of the customer requirements
 - still fulfilling the quality demands

Optimization of a Tertiary Crushing Stage

- small scale optimization

Optimization of a Tertiary Crushing Stage

Background

- Some limestone quarries in the Mid West produce excessive amounts of fines <4# (<4.7mm)
- A typical “modern” crusher produces 19-21%
- A typical “old” crusher produces 14-15%
- Modern crushers have high power input/draw which is achieved by large throws,
BUT these machines produce more fines.

Optimization of a Tertiary Crushing Stage


- The crushers are the last size reduction stage in the value chain.
- Over crushing is common.
- The rock cannot be repaired.
- We need to control the crusher carefully.

Optimization of a Tertiary Crushing Stage





Combine product yield and economic aspects

Test Setup and Parameters


- H3800 Hydrocone
- Standard MC and modified chambers
- Eccentric speed 360->288 rpm
- Throw 36->29 mm



Crusher (Nominal) Geometry





Breakage Modes



- Interparticle

- Single particle

Chamber Design



Parallel crushing zone
with low pressure


Test Procedure

- **Careful calibration**
- **50 tests**
 - CSS=minimum, ..., 14, 15, 16, ...,21 mm
- **Sieving (and shape/flakiness index)**
- **Yield calculations**
- **Cost calculation**
- **Gross profit estimation**


Results from Sieving

Modified, +25-50 feed (coarse) 29 mm stroke, 288 rpm								Modified, +25-50 feed (coarse) 29 mm stroke, 360 rpm -STD								Modified, +25-50 feed (coarse) 36 mm stroke, 360 rpm -STD								
26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	49	50	
0.063	3.4	3	3.1	2	2.4	1.8	1.7	1.6	3.3	2.6	2.3	2.1	2.2	2	1.7	1.5	3	2.5	2.3	2.3	1.9	1.7	1.3	1.5
0.125	6.3	5.6	5.4	3.9	4.2	3.6	3.3	3.1	6.3	4.9	4.5	4.1	4.3	4.1	3.3	2.9	5.4	4.5	4.2	4.5	3.6	3.2	2.7	3.1
0.25	9.9	9.1	7.9	6.3	6.3	5.9	5.1	4.8	10.1	7.7	7.1	6.5	6.9	6.8	5.2	4.6	8.2	7.1	6.7	7.1	5.6	4.9	4.2	4.9
0.5	13.5	12.3	10.3	8.5	8.3	8	6.8	6.4	13.8	10.5	9.5	8.8	9.3	9.2	7	6.3	11.2	9.9	9.1	9.7	7.6	6.7	5.8	6.6
1	18.1	16.2	13.4	11.2	10.9	10.5	8.8	8.5	18.5	14.1	12.7	11.8	12.2	11.9	9.3	8.5	15.4	13.5	12.3	13	10.2	9.1	8.1	8.4
2	26.1	23	19	16.1	15.7	14.8	12.3	12.3	26.5	20.8	18.2	17.2	17.1	16.1	13.5	12.4	22.5	19.5	18.1	18.5	14.5	13.3	12.1	11.9
4	38.3	33.3	28.2	23.9	23.8	21.5	17.8	18.4	38.5	31	27	25.2	24.6	22.3	20.1	18.7	32.8	27.8	26.3	26.4	20.5	19.1	18.1	17.5
5.6	46	42.2	32	31.1	30.5	27.7	22.7	23.6	45	39.8	32.6	32.3	31.6	26	26.2	24	41.3	35.7	31.2	32.5	26.9	23.2	22	21.5
8	62.6	55.8	48.5	41.8	41.3	36.9	29.9	31.7	60.1	52.4	45.4	43.1	40.9	36.1	35.9	32.9	53.2	45	43.8	41.9	33.2	31.7	30.3	29
11.2	81.1	71.7	65.3	57.2	56.6	52	40.9	41.9	74.7	68.6	60.6	56.3	53.8	48.6	48	45.2	68.5	59.7	57.7	53.4	42.1	40	39.5	38.4
16	96.4	92.9	92.6	80.1	83.2	76.5	64.2	62.3	93.5	87.8	86.7	79.2	77	69.3	68.2	65.8	90	81.1	77.1	71.8	58.5	54.4	55.4	54.1
22.4	100	100	100	99.1	97.7	97.3	91.9	93.6	100	98.5	100	100	96.8	92.6	94.2	93.6	100	97.5	95.1	95.4	87.8	86.8	84.4	81.2
25	100	100	100	100	100	100	96.7	94.9	100	100	100	100	100	95.6	100	100	100	100	100	97.5	94.4	93.9	93.4	92.2
31.5	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100

Particle Size Distributions




Total Capacity [tph]




Product Yield

0-2, 2-16 and +16mm, [%]




Production of Premium Product

2-16mm [tph]



Relation between Produced Product and Fines



Economical Analysis

- **Allocated cost per ton saleable product**

- = all the cumulated costs (drilling, blasting, hauling, conveying, primary and secondary crushing) divided by the mass of the saleable product

- **Gross profit**

- = potential sales – production costs

Economical Analysis

Costs	[USD]	Step					
		1	2	3	4	5	6
Feed material		1.30	1.40	1.50	1.60	1.70	1.80
Crushing cost		0.34	0.37	0.40	0.42	0.45	0.47
Income	[USD]						
		4.00	4.80	5.60	6.40	7.20	8.00
Typical product		0.20	0.22	0.24	0.26	0.28	0.30
Handling of fines							

Economical Analysis

29/288									36/360								
CSS [mm]	12.5	14	15	16	17	18	19	20	15.8	17	18	19	20	21	22	23	
P [kw]	133	111	105	89	92	87	79	74	148	123	126	101	100	91	84	80	
p [Mpa]	5.6	4.6	4.0	3.2	3.4	3.0	2.8	2.6	4.6	4.2	3.8	2.7	2.7	2.5	2.2	2.3	
Q [tph]	95	97	101	105	109	109	103	114	120	125	130	137	126	134	134	138	
<i>Yield [%]</i>																	
0-2	26.1	23.0	19.0	16.1	15.7	14.8	12.3	12.3	22.5	19.5	18.1	18.5	14.5	13.3	12.1	11.9	
2-16	70.3	69.9	73.6	64.0	67.5	61.7	51.9	50.0	67.5	61.6	59.0	53.3	44.0	41.1	43.3	42.2	
+16	3.6	7.1	7.4	19.9	16.8	23.5	35.8	37.7	10.0	18.9	22.9	28.2	41.5	45.6	44.6	45.9	
<i>Volumes [tph]</i>																	
0-2	25	22	19	17	17	16	13	14	27	24	24	25	18	18	16	16	
2-16	67	68	74	67	74	67	53	57	81	77	77	73	55	55	58	58	
+16	3	7	7	21	18	26	37	43	12	24	30	39	52	61	60	63	

Economical Analysis

Economics

Step 1

Cost per ton \$/ton

2.24	2.16	2.06	2.04	2.01	2.02	2.01	2.02	2.16	2.12	2.10	2.13	2.08	2.07	2.04	2.04
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

0.94	1.00	1.15	1.02	1.09	0.99	0.84	0.81	0.97	0.91	0.89	0.78	0.67	0.63	0.68	0.67
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour

89	97	116	107	119	108	87	92	116	114	116	107	84	84	92	92
----	----	-----	-----	-----	-----	----	----	-----	-----	-----	-----	----	----	----	----

Step 2

Cost per ton \$/ton

2.41	2.33	2.21	2.19	2.17	2.17	2.16	2.17	2.32	2.28	2.26	2.29	2.24	2.23	2.19	2.19
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

1.50	1.55	1.74	1.53	1.63	1.49	1.25	1.20	1.50	1.40	1.36	1.20	1.02	0.96	1.03	1.00
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour

142	151	176	160	178	162	129	137	180	175	176	165	128	128	138	138
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Step 3

Cost per ton \$/ton

2.59	2.50	2.38	2.36	2.33	2.34	2.33	2.34	2.50	2.45	2.43	2.47	2.42	2.40	2.36	2.37
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

2.05	2.11	2.32	2.04	2.17	1.98	1.67	1.60	2.04	1.89	1.83	1.62	1.37	1.28	1.37	1.34
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour

195	205	235	214	236	215	172	183	244	236	237	222	172	172	184	184
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Step 4

Cost per ton \$/ton

2.75	2.66	2.53	2.51	2.48	2.49	2.47	2.48	2.66	2.61	2.58	2.62	2.57	2.55	2.51	2.51
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

2.50	2.55	2.80	2.45	2.61	2.38	2.01	1.93	2.47	2.29	2.20	1.96	1.65	1.55	1.65	1.61
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour

237	248	283	257	284	259	207	220	296	286	287	269	208	207	221	222
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Step 5

Cost per ton \$/ton

2.93	2.83	2.70	2.67	2.64	2.65	2.64	2.64	2.83	2.78	2.75	2.79	2.73	2.72	2.67	2.67
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

2.93	2.99	3.26	2.85	3.03	2.77	2.33	2.24	2.89	2.67	2.57	2.30	1.92	1.81	1.93	1.88
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour

278	290	329	300	331	302	240	256	346	334	335	315	243	242	258	259
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Step 6

Cost per ton \$/ton

3.09	2.99	2.85	2.82	2.79	2.79	2.78	2.79	2.99	2.93	2.90	2.95	2.88	2.87	2.82	2.82
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/ton

3.37	3.43	3.74	3.27	3.47	3.17	2.67	2.57	3.31	3.06	2.95	2.64	2.21	2.07	2.21	2.15
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Gross profit \$/hour


320	333	377	343	378	345	275	293	398	383	384	361	278	277	296	297
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

29/288


36/360

Allocated cost for saleable products \$/ton


Step 1, Allocated cost per ton




Step 6, Allocated cost per ton



Gross profit - \$/ton




Gross profit - \$/hour




Yield

0-2, 2-16 and +16mm, [%]



Particle Size Distributions



Conclusions Optimization of a Crushing Stage

- Difficult to observe the differences from PSD graphs
- Careful analyses of yield required
- Maximize yield
 - Get in control of your process!
 - Frequent (=daily) calibration
 - Improved process control
 - Active choice of optimal CSS
- 25% decrease in total capacity
- 30% increase in yield of premium product
- Gentle crushing is the key to maximizing the overall yield in a situation where the fines has a low value

www.quarryacademy.com



Improving Processes. Instilling Expertise.

DYNO
Dyno Nobel



SANDVIK